

INTERLUDE XL

9/16" Dimensional Tee System



Physical Data

Material

Hot dipped galvanized steel

Surface Finish

Baked polyester paint

Cross Tee/Main Beam Interface

Flush fit and center protrusion

End Detail

Main Beam: Coupling

Cross Tee: Staked-on clip

Seismic Performance

MAIN BEAMS	MINIMUM LBS. TO PULL OUT COMPRESSION/TENSION
6100	329.0

CROSS TEES	MINIMUM LBS. TO PULL OUT COMPRESSION/TENSION
XL6110, XL6120, XL6140 XL6180, XL6190	373.0

Warranty

See pages 104-105 for details



INTERLUDE XL with 1' x 4' light fixture



ULTIMA with INTERLUDE XL 9/16" Dimensional Tee grid



INTERLUDE XL
9/16" Dimensional
Tee System



INTERLUDE
Main Beam



INTERLUDE XL
Cross Tee



INTERLUDE XL

9/16" Dimensional Tee System



Key Selection Attributes

- Hot dipped galvanized coating inhibits red rust better than electrogalvanized or painted systems
- XL staked-on end detail provides secure locked connection
- Rotary-stitched during manufacture by a patented method** for additional torsional strength and extra stability during installation
- Unlimited intersections for flexibility of cross tee placement
- Accommodates virtually any fixture, especially 1' x 4' light fixtures
- 10-year limited warranty; 15-year limited warranty with **HumiGuard Plus** products

Typical Applications

- Offices
- Lobbies and corridors
- Conference rooms
- Retail
- Hospitality

Recycled Content:
25%



Visual Selection

Performance Selection

GRID FACE	ITEM NUMBER	DESCRIPTION	DIMENSIONS	HANGER SPACING* LBS./LIN. FT.				FIRE/FLAME	FIRE GUARD ITEM #	FIRE GUARD HANGER SPACING* LBS./LIN. FT.		ASTM/DUTY CLASS
				1 Ft.	2 Ft.	4 Ft.	5 Ft.			4 Ft.	5 Ft.	
INTERLUDE XL												
9/16"	6100	12' ID Main Beam	144 x 9/16 x 1-3/4"	-	-	12.6	-	-	-	-	-	ID
9/16"	XL6140	4' Cross Tee	48 x 9/16 x 1-3/4"	-	-	12.6	-	-	-	-	-	-
9/16"	XL6120	2' Cross Tee	24 x 9/16 x 1-3/4"		72.5	-	-	-	-	-	-	-
9/16"	XL6110	1' Cross Tee	12 x 9/16 x 1-3/4"	63.0	-	-	-	-	-	-	-	-
9/16"	XL6180	8' Cross Tee	96 x 9/16 x 1-3/4"	-	-	12.6	-	-	-	-	-	-
9/16"	XL6190	6' Cross Tee	72 x 9/16 x 1-3/4"	-	-	12.6	-	-	-	-	-	-
Molding												
9/16"	7804	12' Hemmed Angle Molding	144 x 9/16 x 7/8"	-	-	-	-	-	-	-	-	-
9/16"	7873	10' Shadow Molding	120 x 9/16 x 15/16 x 3/8"	-	-	-	-	-	-	-	-	-


* Simple Span

** U.S. and Foreign Patents 5,979,055; 6,178,712


ASTM Class
HD - Heavy-duty
ID - Intermediate-duty
LD - Light-duty

Details


INTERLUDE Main Beam



INTERLUDE XL Cross Tee



Angle Molding



Shadow Molding

