


# SL2 Plank Grid Component

## ↳ Semi-concealed SL2 Component & Installation



### Semi-concealed SL2

Plank Length (mm)	Products Description	Item Number	LxWxH (mm)	pcs/ctn
1200	Peakform 888 Main Beam	BP734252P	3000X24X35	20
	Concealed T Shape Cross Tee	BP743052P	1200x24x35	60
	Stabilizer Bar	BP7431	1200x22x22	30
1500	Prelude Peakform Main Beam	BP734042	3600X24X43	20
	Concealed T Shape Cross Tee	BP743642	1500x24x43	20
	Stabilizer Bar	BP7436	1500x22x22	30
1800	Prelude Peakform Main Beam	BP734042	3600X24X43	20
	Concealed T Shape Cross Tee	BP743442	1800X24X43	20
	Stabilizer Bar	BP7434	1800x22x22	30
2100	Prelude Peakform Main Beam	BP734042	3600X24X43	20
	Concealed T Shape Cross Tee	BP747342	2100X24X43	20
	Stabilizer Bar	BP7473	2100x22x22	30
2400	Prelude Peakform Main Beam	BP734042	3600X24X43	20
	Concealed T Shape Cross Tee	BP747042	2400X24X43	20
	Stabilizer Bar	BP7470	2400x22x22	30
Corridor	Aluminum Wall Molding	BP784007A	3600X16X8X8X28	30

#### Remark:

- 1 Corridor: aluminum special wall molding must be applied to support the ceiling system if without hang on the cross tee
- 2 Hanger wire: must be added on the concealed T shape cross tee at the space every 1200mm if plank length is over 1500mm.
- 3 All other equipment: such as lights, ducts, airconditioners etc. must be hung independently.